

**Technical Data Sheet**

# Interflon Fin 25 Additive

Engine oil additive for petrol, diesel and gas engines

Engine oil additive containing Interflon's MicPol® Technology. Suitable for enriching virtually all types of mineral and synthetic engine oils used in most engines operating on petrol, diesel, (LPG) and gas.

Reduces engine friction during start-up and operation and improves compression for more engine power, less wear and less engine noise. Makes engines start quicker, run smoother and reduces oil and fuel consumption.

**Applications**

For use in petrol, diesel and (LPG) gas engines of cars, trucks, busses, motorbikes, agricultural and construction equipment, forklifts, lawn-mowers, power generators, piston compressors and many other types of vehicles and machines.

**Advantages**

- ⦿ Reduces oil consumption and improves fuel economy
- ⦿ Extends oil change life
- ⦿ Gives more power and a smoother running engine
- ⦿ Reduces wear
- ⦿ Makes cold engines start-up easier

**Instructions for use**

Shake before use. Change oil and filters when the oil is in a bad condition. Add 2-4% (6% for heavily contaminated engines) after each oil change and let the motor run idle or go driving for at least 15 minutes.

Property	Result	Method
Composition	Mixture of mineral oils, additives and MicPol®	
Colour	White	
Odour	Like oil	
Density 20°C	0.92 g/cm <sup>3</sup>	
Kinematic viscosity 40°C	713 cSt	ASTM D445
Lowest application temperature	-20°C	
Highest application temperature	150°C	
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	3 years	
Particle size MicPol	0.05-15 µm	
Suitable for filters	>20 µm	

\* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

*This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.*