

## Technical Data Sheet

# Interflon Fin Super (aerosol)

### Universal dry-film lubricant

Dry lubricant with MicPol® Technology, with very good cleaning, lubricating and protective action. Penetrates, dissolves dirt, expels moisture and lubricates better and longer than conventional oils. Leaves a clean, dry lubricating film that does not drip, stain, adhere to dust or dirt and provides a long-term protection against moisture and corrosion.

### Applications

Suitable for cleaning, removing rust and corrosion. For the lubrication of chains, cables, housings, cylinders, spindles, hinges, shafts, rods, locks, tools, valves, sunroofs, measuring equipment, door seals, weapons etc. Excellent replacement for lubricants with MoS<sub>2</sub> or graphite and silicon spray.

### Advantages

- ⊖ Reduction of wear
- ⊖ Water resistant
- ⊖ Economic in use
- ⊖ Prevents moving parts/locks from freezing
- ⊖ Colourless/leaves no stains
- ⊖ Dissolves rust and frees sticking parts+
- ⊖ Cleans and protects against corrosion
- ⊖ Contains no chlorinated solvents or silicones
- ⊖ Aerosol can also be used in an upside down (vertical) position
- ⊖ PFAS free

### Instructions for use

Shake before use. Parts should be cleaned first with a solvent or alkaline cleaning agent. Use aerosol from a vertical (upright or upside down) position only. Spray Interflon Fin Super (aerosol) onto parts such as cables and chains and allow to penetrate. Wipe off the excess lubricant with a clean cloth.

Note: Do not use too much Interflon Fin Super (aerosol). Applying a thin layer, with occasional re-lubrication, gives a better result than a thick layer.

Property	Result	Method
Composition	Mixture of mineral and vegetable oils, additives and Micpol®	
Colour	Yellowish brown	
Odour	Like oil	
Density 20°C	0.84 g/cm <sup>3</sup>	
Dynamic viscosity 20°C	64 mPas	ASTM D2983
Kinematic viscosity 40°C	23 cSt	ASTM D445
Lowest application temperature	-43°C	
Highest application temperature**	170°C	
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	6 years	
Conductivity	>2000 pS/m	ASTM D2624
Dielectric strength	88 kV/cm	IEC 60156
Friction coefficient	0.02-0.06 (MicPol®)	

\* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality. \*\* High temperature limit is valid after evaporation of solvent.

*This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.*