

## Technical Data Sheet

# Interflon Food Lube G320

### Heavy duty, multi-purpose CLP oil

Multi-purpose, heavy duty CLP oil with MicPol® Technology. Specially formulated for the lubrication and protection of oil lubricated machine parts including gearboxes, drive and transport chains and guide ways exposed to high loads or operating under wet or adverse conditions.

Fortified with MicPol® Technology for increased lubricity and durability. Strongly penetrates to significantly reduce friction and wear from within. Reduces power consumption and increases the service life of critical components.

Interflon Food Lube G320 is listed by the NSF for the use in applications with incidental food contact.

### Applications

For lubricating and protecting chains, industrial gearboxes, guide ways, slides, injection moulding machinery and many other oil lubricated machine parts in the food processing and heavy industries.

### Advantages

- ⦿ Excellent protection against wear, even at high loads
- ⦿ Resists water and dirt and prevents corrosion
- ⦿ Reduces power consumption
- ⦿ Reduced elongation and longer service life of chains
- ⦿ Longer gearbox oil life at reduced oil temperatures
- ⦿ PFAS free

### Instructions for use

Shake or stir before use according to the size of the packaging. Drain the oil from the system as prescribed by the manufacturer prior to use.

| Property                        | Result                                                                                                       | Method          |
|---------------------------------|--------------------------------------------------------------------------------------------------------------|-----------------|
| Composition                     | Mixture of mineral and synthetic oils, additives and Micpol®                                                 |                 |
| Colour                          | Colourless                                                                                                   |                 |
| Odour                           | Like oil                                                                                                     |                 |
| Density 20°C                    | 0.87 g/cm <sup>3</sup>                                                                                       |                 |
| Kinematic viscosity 40°C        | 320 cSt                                                                                                      | ASTM D445       |
| Lowest application temperature  | -10°C                                                                                                        |                 |
| Highest application temperature | 100°C                                                                                                        |                 |
| Manufacturing date              | The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing. |                 |
| Shelf life*                     | 4 years                                                                                                      |                 |
| Base oil viscosity index        | 122                                                                                                          | ASTM D2270      |
| FZG A8390                       | >12                                                                                                          | DIN ISO 14635-1 |
| ISO VG                          | 320                                                                                                          |                 |
| Shear stability                 | <-6%                                                                                                         | CEC-L45-A-99    |
| NSF registration number         | 128800                                                                                                       |                 |
| NSF                             | H1                                                                                                           |                 |
| ISO 21469                       | Yes                                                                                                          |                 |
| Halal                           | Yes                                                                                                          |                 |
| Kosher                          | Yes                                                                                                          |                 |

\* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

*This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.*