

## Technical Data Sheet

# Interflon Food Lube G (aerosol)

## Lubricant for heavy applications

Strong penetrating lubricant with Interflon MicPol® Technology for heavy loaded chains and guide ways.

Interflon Food Lube G (aerosol) is listed by the NSF for the use in applications with incidental food contact.

### Applications

For lubrication and protection of chains and guide ways in machines for the manufacture, processing, packaging and transportation of food. Suitable for applications where there is (occasional) contact with water.

### Advantages

- ⦿ Has EP-properties
- ⦿ Excellent penetration
- ⦿ Protects chains and guide ways against moisture, wear and rust
- ⦿ Withstands water
- ⦿ Aerosol can also be used in an upside down (vertical) position
- ⦿ PFAS free

### Instructions for use

Shake well before use. Use aerosol from a vertical (upright or upside down) position only. Parts should be cleaned first with a solvent or alkaline cleaning agent. Spray Interflon Food Lube G (aerosol) onto parts and allow to penetrate. Wipe off the excess lubricant with a clean cloth.

Note: Do not use too much Interflon Food Lube G (aerosol). A thin layer, with occasional re-application now and again, works better than a thick layer.

Property	Result	Method
Composition	Mixture of mineral and vegetable oils, additives and MicPol®.	
Colour	Beige	
Odour	Like oil	
Density 20°C	0.87 g/cm <sup>3</sup>	
Kinematic viscosity 40°C	260 cSt	ASTM D445
Lowest application temperature	-10°C	
Highest application temperature**	100°C	
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	6 years	
NSF registration number	136508	
NSF	H1	
ISO 21469	Yes	
Halal	Yes	
Kosher	Yes	

\* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality. \*\* High temperature limit is valid after evaporation of solvent.

*This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.*