

acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

 Version number:
 Date of issue
 Revision:

 6.0
 2022-12-05
 2022-12-05.

Replaces version: (4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Interflon Dry Clean Stainless Steel (Aerosol)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Scope cleaning agent

1.3 Details of the supplier of the safety data sheet

Interflon BV Belder 47 4704 RK Roosendaal Netherlands

Telephone: +31 (0)165 553911 e-mail: Service@Interflon.com Website: www.Interflon.com

e-mail (competent person) msds.uk@interflon.com

1.4 Emergency telephone number

Poison centre								
Country	Name	Postal code/ city	Telephone	Telefax	Opening hours			
United Kingdom	UK National Poison Centre		UK National Poisons Emergency number: +44 870 600 6266		Mon - Fri 12:00 AM - 11:00 PM			

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.3	aerosols	1	Aerosol 1	H222,H229

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling

- Signal word.

danger

- Pictograms

GHS02



- Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

United Kingdom: en Page: 1 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

 Version number:
 Date of issue
 Revision:

 6.0
 2022-12-05
 2022-12-05.

Replaces version: (4)

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Additional labelling according to Directive 75/324/EEC relating to aerosol dispensers

Extremely flammable. Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Product description

Mixture of solvents, surface-active substances and water

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
butane	CAS No 106-97-8	10 - < 25	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) K(b)
	EC No 203-448-7			
	Index No 601-004-00-0			
Hydrocarbons, C11-C14, n-al- kanes, isoalkanes, cyclic, <2% aromatics	CAS No 64742-47-8	5 – < 10	Asp. Tox. 1 / H304	
aromatics	EC No 926-141-6			
Propane	CAS No 74-98-6	1 – < 5	Flam. Gas 1 / H220 Press. Gas L / H280	
	EC No 200-827-9			
	Index No 601-003-00-5			

United Kingdom: en Page: 2 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Date of issue Version number: Revision: 6.0 2022-12-05 2022-12-05.

Replaces version: (4)

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
isobutane	CAS No 75-28-5	1-<5	Flam. Gas 1 / H220 Press. Gas C / H280	C(a) GHS-HC U
	EC No 200-857-2			, c
	Index No 601-004-00-0			

Notes

C(a): Mixture of isomers

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC,

K(b): The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w 1,3-butadiene (EINECS No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements

(P102-) P210-P403 should apply
When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, lique-U: fied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Regulation 648/2004/EC on detergents

Wt%	Constituents	Weight % content (or range)
≥30%	aliphatic hydrocarbons	30 % and more

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 **Description of first aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

Indication of any immediate medical attention and special treatment needed 4.3

none

United Kingdom: en Page: 3 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

 Version number:
 Date of issue
 Revision:

 6.0
 2022-12-05
 2022-12-05.

Replaces version: (4)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water mist, Fire extinguishing powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.

United Kingdom: en Page: 4 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

 Version number:
 Date of issue
 Revision:

 6.0
 2022-12-05
 2022-12-05.

Replaces version: (4)

7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.

Further information on storage conditions

Keep container tightly closed. Store in a well-ventilated place. Keep cool. Protect from sunlight.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Source
United Kingdom	butane	106-97-8	600	1,450	750	1,810			EH40/2005

Notation

Ceiling-C STEL ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

National limit values

Country	Name of agent	CAS No	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Source
United Kingdom	butane	106-97-8	600	1,450	750	1,810			EH40/2005

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Occupati	Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of agent	CAS No	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Source
United Kingdom	butane	106-97-8	600	1,450	750	1,810			EH40/2005

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

United Kingdom: en Page: 5 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number: Date of issue Revision: 6.0 2022-12-05 2022-12-05.

Replaces version: (4)

STEL

Notation

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

Country	Name of agent	CAS No	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Source
United Kingdom	butane	106-97-8	600	1,450	750	1,810			EH40/2005

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identi- fier		TWA [mg/m³]	STEL [ppm]		Ceiling-C [mg/m³]	Source
GB	butane	106-97-8	WEL	600	1,450	750	1,810		EH40/ 2005

Notation

Ceiling-C

TWA

ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

8.2 **Exposure controls**

General safety precautions

Use only in well-ventilated areas.

In case of insufficient ventilation, wear suitable respiratory equipment.

Avoid contact with skin and eyes.

Keep away from food, drink and animal feedingstuffs. Wash hands after use. Do not breathe gas/fumes/vapour/

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection.

Skin protection

- Hand protection

Not required.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

United Kingdom: en Page: 6 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)2022-12-05.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid, gaseous (spray aerosol)
Colour	light brown
Odour	characteristic
Melting point/freezing point	-187.6 °C at 1,013 hPa
Boiling point or initial boiling point and boiling range	-44.5 °C
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	0.5 vol% - 8.5 vol%
Flash point	-60 °C
Auto-ignition temperature	not determined
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not relevant
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available

Vapour pressure	2,100 hPa at 20 °C
-----------------	--------------------

Density and/or relative density

Density	0.84 ^g / _{cm³} at 20 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

United Kingdom: en Page: 7 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

 Version number:
 Date of issue
 Revision:

 6.0
 2022-12-05
 2022-12-05.

Replaces version: (4)

9.2 Other information

Information with regard to physical hazard classes

Aerosols

- Components (flammable)	39.96 %
Other safety characteristics	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

United Kingdom: en Page: 8 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

 Version number:
 Date of issue
 Revision:

 6.0
 2022-12-05
 2022-12-05.

Replaces version: (4)

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

United Kingdom: en Page: 9 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)2022-12-05.

Relevant provisions relating to waste

List of wastes

- Product

14 06 03* other solvents and solvent mixtures

15 01 04 metallic packaging

16 05 04* gases in pressure containers (including halons) containing hazardous substances

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID UN 1950 IMDG-Code UN 1950 ICAO-TI UN 1950

14.2 UN proper shipping name

ADR/RID AEROSOLS IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

ADR/RID 2 (2.1)
IMDG-Code 2.1
ICAO-TI 2.1

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information

Classification code 5F
Danger label(s) 2.1



Special provisions (SP) 190, 327, 344, 625

Excepted quantities (EQ) E0

United Kingdom: en Page: 10 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number: 6.0	Date of issue 2022-12-05	Revision 2022-12-05
Replaces version: (4)	2022-12-03	2022-12-03
Limited quantities (LQ)	1 L	
Transport category (TC)	2	
Tunnel restriction code (TRC)	D	
Regulations concerning the Inte Additional information	ernational Carriage of Dangerous Goo	ds by Rail (RID) -
Classification code	5F	
Danger label(s)	2.1	
Special provisions (SP)	190, 327, 344, 625	
Excepted quantities (EQ)	EO	
Limited quantities (LQ)	1 L	
Transport category (TC)	2	
Hazard identification No	23	
International Maritime Danger	ous Goods Code (IMDG) - Additional in	formation
Marine pollutant	-	
Danger label(s)	2.1	
Special provisions (SP)	63, 190, 277, 327, 344	, 381, 959
Excepted quantities (EQ)	EO	
Limited quantities (LQ)	1 L	
EmS	F-D, S-U	
Stowage category	-	
International Civil Aviation Org	anization (ICAO-IATA/DGR) - Additiona	al information
Danger label(s)	2.1	
Special provisions (SP)	A145, A167	
Excepted quantities (EQ)	EO	
Limited quantities (LQ)	30 kg	
Excepted quantities (EQ)	EO	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom: en Page: 11 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

 Version number:
 Date of issue
 Revision:

 6.0
 2022-12-05
 2022-12-05.

Replaces version: (4)

Relevant provisions of the European Union (EU)

Seveso Directive

2012/	2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories Qualifying quantity (tonnes) for the application of lower and upper-tier requirements			
P3a	flammable aerosols (containing Flam. Gas or Flam. Liq.)	150	500	46)

Notation

Industrial Emissions Directive (IED)

VOC content	23 %

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

United Kingdom: en Page: 12 / 19

^{46) &#}x27;flammable' aerosols category 1 or 2, containing flammable gases category 1 or 2 or flammable liquids category 1 Note: qualifying quantity = net



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)2022-12-05.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
1.1	Registration number (REACH): not relevant (mixture)		yes
1.1	Unique formula identifier UFI: X520-70PV-D00D-7QCS		yes
1.3	e-mail (competent person): Service@interflon.com (Service lab)	e-mail (competent person): msds.uk@interflon.com	yes
2.1	Classification according to Regulation (EC) No 1272/2008 (CLP)	Classification acc. to GHS	yes
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.2	Labelling according to Regulation (EC) No 1272/ 2008 (CLP)	Labelling	yes
2.3	Other hazards	Other hazards: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.		yes
3.2		Hazardous ingredients: change in the listing (table)	yes
3.2	Regulation 648/2004/EC on detergents		yes
3.2		Regulation 648/2004/EC on detergents: change in the listing (table)	yes
3.2		Regulation 648/2004/EC on detergents	yes
3.2		Regulation 648/2004/EC on detergents: change in the listing (table)	yes
5.1	Suitable extinguishing media: Water spray, BC-powder	Suitable extinguishing media: Water mist, Fire extinguishing powder	yes
5.3	Advice for firefighters: In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.	Advice for firefighters: In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.	yes
7.1	Advice on general occupational hygiene: Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.	Advice on general occupational hygiene: Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.	yes

United Kingdom: en Page: 13 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
7.2	- Flammability hazards: Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	- Flammability hazards: Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.	yes
8.1		Occupational exposure limit values (Workplace Ex- posure Limits): change in the listing (table)	yes
8.2	Eye/face protection: Wear eye/face protection. Use safety goggle with side protection.	Eye/face protection: Use safety goggle with side protection.	yes
9.1	Appearance		yes
9.1	Physical state: aerosol (spray aerosol)	Physical state: liquid, gaseous (spray aerosol)	yes
9.1	Other safety parameters		yes
9.1	Initial boiling point and boiling range	Boiling point or initial boiling point and boiling range	yes
9.1	Flammability (solid, gas)	Flammability	yes
9.1	Explosive limits	Lower and upper explosion limit: 0.5 vol% - 8.5 vol%	yes
9.1	Evaporation rate: not determined		yes
9.1	Lower explosion limit (LEL): 0.5 vol%		yes
9.1	Upper explosion limit (UEL): 8.5 vol%		yes
9.1		Decomposition temperature: not relevant	yes
9.1		Kinematic viscosity: not relevant	yes
9.1	- n-octanol/water (log KOW)	Partition coefficient n-octanol/water (log value)	yes
9.1		Density and/or relative density	yes
9.1	Vapour density: this information is not available		yes
9.1	Viscosity: not relevant (aerosol)		yes
9.1	Explosive properties: none		yes
9.1	Oxidising properties: none		yes
9.1		Relative vapour density: information on this property is not available	yes
9.1		Particle characteristics: not relevant (aerosol)	yes
9.2	Propellant content: 29.97 %		yes

United Kingdom: en Page: 14 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
9.2		Information with regard to physical hazard classes	yes
9.2		Aerosols	yes
9.2		Components (flammable): 39.96 %	yes
9.2		Other safety characteristics: there is no additional information	yes
11.1	Classification according to GHS (1272/2008/EC, CLP)	Classification acc. to GHS	yes
11.2		Information on other hazards: There is no additional information.	yes
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes
12.6	Endocrine disrupting potential	Endocrine disrupting properties	yes
12.7	Other adverse effects	Other adverse effects: Data are not available.	yes
14.1	UN number: 1950	UN number or ID number	yes
14.1		ADR/RID: UN 1950	yes
14.1		IMDG-Code: UN 1950	yes
14.1		ICAO-TI: UN 1950	yes
14.2	UN proper shipping name: AEROSOLS	UN proper shipping name	yes
14.2		ADR/RID: AEROSOLS	yes
14.2		IMDG-Code: AEROSOLS	yes
14.2		ICAO-TI: Aerosols, flammable	yes
14.3	Class: 2 (gases) (aerosol)		yes
14.3	Subsidiary risk(s): 2.1 (flammable)		yes
14.3		ADR/RID: 2 (2.1)	yes
14.3		IMDG-Code: 2.1	yes
14.3		ICAO-TI: 2.1	yes
14.4	Packing group: not assigned to a packing group	Packing group: not assigned	yes

United Kingdom: en Page: 15 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)2022-12-05.

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
14.7	Transport in bulk according to Annex II of MAR- POL and the IBC Code	Maritime transport in bulk according to IMO instruments	yes
14.7	Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN)	Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: AEROSOLS		yes
14.7	Class: 2		yes
14.7		Regulations concerning the International Car- riage of Dangerous Goods by Rail (RID) - Addition- al information	yes
14.7		Classification code: 5F	yes
14.7		Danger label(s): 2.1	yes
14.7		Danger label(s): change in the listing (table)	yes
14.7		Special provisions (SP): 190, 327, 344, 625	yes
14.7		Excepted quantities (EQ): E0	yes
14.7		Limited quantities (LQ): 1 L	yes
14.7		Transport category (TC): 2	yes
14.7		Hazard identification No: 23	yes
14.7	International Maritime Dangerous Goods Code (IMDG)	International Maritime Dangerous Goods Code (IMDG) - Additional information	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: AEROSOLS		yes
14.7	Class: 2.1		yes
14.7	International Civil Aviation Organization (ICAO- IATA/DGR)	International Civil Aviation Organization (ICAO- IATA/DGR) - Additional information	yes
14.7	UN number: 1950		yes
14.7	Proper shipping name: Aerosols, flammable		yes
14.7	Class: 2.1		yes

United Kingdom: en Page: 16 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)2022-12-05.

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
15.1	Restrictions according to REACH, Annex XVII		yes
15.1		Dangerous substances with restrictions (REACH, Annex XVII): change in the listing (table)	yes
15.1	List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list: none of the ingredients are listed		yes
15.1	Directive on industrial emissions (VOCs, 2010/75/EU)	Industrial Emissions Directive (IED)	yes
15.1	Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II	Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)	yes
15.1	Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)	Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)	yes
15.1		Regulation on persistent organic pollutants (POP): None of the ingredients are listed.	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16	Key literature references and sources for data: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU.Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	Key literature references and sources for data: Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Danger- ous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).	yes
16	List of relevant phrases (code and full text as stated in chapter 2 and 3)	List of relevant phrases (code and full text as stated in section 2 and 3)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)	
Asp. Tox.	Aspiration hazard	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)	
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)	
EINECS	European Inventory of Existing Commercial Chemical Substances	

United Kingdom: en Page: 17 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)2022-12-05.

Abbr.	Descriptions of used abbreviations	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
Flam. Gas	Flammable gas	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
ppm	Parts per million	
Press. Gas	Gas under pressure	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and very Bioaccumulative	
WEL	Workplace exposure limit	

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

United Kingdom: en Page: 18 / 19



acc. to Regulation (EC) No. 1907/2006 (REACH)

Interflon Dry Clean Stainless Steel (Aerosol)

Version number:Date of issueRevision:6.02022-12-052022-12-05.Replaces version: (4)2022-12-05.

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom: en Page: 19 / 19