

## Technical Data Sheet

# Interflon Eco EM100+

### Human and environmentally friendly cleaner

Biodegradable cleaner for metal parts, with outstanding cleaning abilities and a very high flashpoint. Contains unique, non-evaporating active substances (no volatile organic compounds) for safely dissolving heavy greases, oils, dirt, graphite and other carbonized residues. Removes ink, tar, polymers, adhesives, waxes and bitumen. Leaves a light coating of oil behind, providing protection against flash rust. No extraction system needed for use in enclosed spaces. Problem-free application in agriculture, forestry, factories, sewage plants, etc.

Interflon Eco EM100+ is listed by the NSF for use in the food industry as a general cleaner.

### Applications

Highly universal, for practically every cleaning job including engines, gearboxes, chains (including dip cleaning), cogwheels, conveyors, bearings, slides, crane masts, building and agricultural equipment, machines and machine parts, firearms and many other metal parts, objects and surfaces. Suitable for the use in cleaning benches.

### Advantages

- ⦿ Excellent cleaning and degreasing abilities
- ⦿ Very high flash point to eliminate the risk of fire
- ⦿ Protects cleaned parts from flash rust
- ⦿ ATEX and ADR exempt
- ⦿ Composed from renewable resources
- ⦿ Readily biodegradable with low eco-toxicity to minimize impact on man and the environment

### Instructions for use

Apply cleaner at full. It is advisable to test a small inconspicuous area to make sure that the cleaning agent does not adversely affect or damage the surface being cleaned. Do not apply to hot surfaces. When cleaning large vertical areas, apply the product from the bottom and work upwards ensuring that the whole area is covered. Cleaning away any dirt is best done from the bottom in an upward direction to prevent leaving any streak marks.

Property	Result	Method
Composition	Mixture of solvents and additives	
Colour	Light yellow	
Odour	Characteristic	
Density 20°C	0.87 g/cm <sup>3</sup>	
Dynamic viscosity 20°C	27 mPas	ASTM D2983
Highest application temperature	70°C	
Biodegradability	80%	ASTM D7373
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	2 years	
Evaporation speed	1000 (ether = 1)	
Vapour pressure 20°C	0.01 hPa	
NSF registration number	141221	
NSF	K1, K3	
Halal	Yes	
Kosher	Yes	

\* Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.