

Technical Data Sheet

Interflon Fin Clean All²

Deep cleaning alkaline label-free cleaner with "1001" applications

Versatile, highly alkaline, label-free deep enzymatic cleaner with F-Active Technology for a wide range of applications. Highly concentrated, very effective and very economical to use (dilutable up to 1:200). Suitable for use in the pharmaceutical, food & drink and other industries

Interflon Fin Clean All² is included in the list by the NSF for use in the food processing industry as a general cleaner.

Applications

Ideal universal cleaner for almost all applications, such as cleaning machines, floors and walls, etc., also in the food processing and pharmaceutical industries. Suitable for cleaning both the outside and inside of vehicles. Also suitable for removing transport wax.

Advantages

- Leaves no residue after rinsing
- Economical in use
- Biodegradable
- Ocontains renewable raw materials
- Supplied as a concentrate
- O Does not contain NTA, EDTA
- No hazard pictograms (label-free)
- Not ADR classified
- Light anti-corrosive properties

Instructions for use

Depending on the application, apply Interflon Fin Clean All² concentrated or diluted to 1:200 (see page 2 of the Technical Data Sheet for an overview of dilutions). Allow the product to work, then clean the surface with a brush, sponge or cloth. Do not allow the surface to dry because under certain circumstances a grey residue is left behind. Rinse with water. It is advisable to test the cleaner in an inconspicuous area to ensure that the cleaner does not damage the surface to be cleaned.

Apply the cleaner to vertical surfaces from bottom to top with overlaps to prevent dripping traces. To clean / remove dirt, work from top to bottom to avoid streaks.

Before cleaning with Interflon Fin Clean All^2 in the food processing industry, remove or cover all food products and packaging. After cleaning in the food processing industry, rinsing with drinking water is required. Never allow the product to dry and never process it in direct sunlight

Property	Result	Method
Composition	Mixture of surface-active substances, enzymes and water	
Colour	Light yellow	
Odour	Characteristic	
Density 20°C	1.01 g/cm3	
Highest application temperature	70 °C	
pH 1% 20°C	8.9	
Biodegradability	> 60%	OECD 301D
Manufacturing date	The batch number consists of a 8-digit number. The first 4 numbers represent the YY/MM of the manufacturing.	
Shelf life*	2 years	
Vapour pressure 20°C	23.5 hPa	
NSF registration number	158201	
NSF	A1	
Halal	Yes	
Kosher	Yes	

^{*} Shelf life of the product in original and unopened packaging. Storage temperatures <0°C need to be avoided to guarantee product quality.

www.interflon.com 04/11/2025



Technical Data Sheet

Interflon Fin Clean All²

Deep cleaning alkaline label-free cleaner with "1001" applications

Applications	Interflon Fin Clean All ²	Applications	Interflon Fir Clean All²
Floors general	1:50 - 1:200	Outdoor cleaning	
Workshop floors	1:3 - 1:50	General 1:5 - 1:100	
Doors	1:20 -1:200	Cabin	1:5 - 1:100
Tables	1:20 -1:200	Chassis	1:5 - 1:100
Walls	1:20 -1:200	Tarpaulins	1:5 - 1:100
Windows	1:20 -1:200	Aluminium	1:5 - 1:100
Carpets	conc 1:20	Prevents algal deposits* 1:10	
Steel and iron parts	1:5 - 1:100	Facade frames	1:10 - 1:15
Aluminium	1:5 - 1:100	Subfloor	1:5 - 1:100
Non-ferrous metal	1:10- 1:100	Insect remover	1:10
Fly rust remover	1:10- 1:100	Trams	1:5 - 1:50
Cleaner for metal-washing equipment	1:3- 1:100	Construction machinery	1:5 - 1:10
E.g. <u>Bubi</u> Cleaner		Containers	1:5 - 1:50
Ultrasonic cleaning	1:10 - 1:50	Agricultural machines	1:5 – 1:20
and the state of t		Grass-maize-beet juice	1:5 - 1:15
Sanitary cleaning		Vegetable and fruit juice	1:10 - 1:15
Floor and wall tiles etc.	1:50-1:100	Caravans	1:5 - 1:50
with disinfection and limescale removal			
Lime, urine and limescale removal		Outdoor cleaning	
		General	1:100
Car wash		Nicotine cleaner	Conc 1:10
Tile cleaning	1:50-1:100	Glass cleaner	1:1000
Outdoor repellent		Cold cleaner	1:3 - 1:100
Brush <u>washers</u>	1:5 - 1:50	Removal of preservative wax	1:3
		Vehicles	
		Rims, engine	1:5 - 1:15
-		Bodywork	1:10 - 1:30
		Engine	1:10 - 1:30
		Windows	1:70
		Snow chains	

This information is based on our best and present knowledge and intended to provide general notes about the product and intended use. Therefore it shouldn't be construed as guaranteeing properties of the product described or suitability for an application. Any existing industrial property rights must be observed. Quality of our products is guaranteed under our General Conditions of Sale. Interflon® and MicPol® are registered trademarks of Interflon BV. Typical properties mentioned in this document are based on our production tolerances and do not represent a specification. Variations that do not affect product performance are to be expected during normal manufacturing. Information provided in this document is subject to change without notice in advance.

www.interflon.com 04/11/2025 2